

PH Series

• 5~35°C 5,000Times.

- Non-solvent proof.
- For photo flash.
- RoHS compliant.

SPECIFICATIONS

Item	Characteristics			
Rated Voltage	330 V _{DC}			
Operating Temperature Range	-20 ~ +55°C			
Capacitance Tolerance	-10 ~ +20% (V) (at 20°C, 120Hz)			
Leakage Current	I=1×C Where, I: Leakage current (μA) C: Nominal capacitance (μF) (at 20°C, 5 minutes)			
Dissipation Factor (Tanδ)	Cap. ≤ 600μF	0.10	(at 20°C, 120Hz)	
	Cap. > 600μF	0.15		
Charge and Discharge Characteristics	<p>The following specifications shall be satisfied when the capacitors are restored to 20°C after charge and discharge are repeated 5,000 times at room temperature. (5 to 35°C)</p> <p>Charge voltage: rated voltage Charge and discharge cycles: 30 seconds Discharge resistance or Xenon tube: about 1Ω</p> <p>Capacitance change ≤ ±10% of the initial value Tanδ ≤ 150% of the initial specified value Leakage current ≤ 150% of the initial specified value</p>			
Shelf Life	<p>The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them at 55°C for 1,000 hours without voltage applied.</p> <p>Capacitance change ≤ ±10% of the initial value Tanδ ≤ 150% of the initial specified value Leakage current ≤ 300% of the initial specified value</p>			
Others	Satisfied EIAJ RC-3801A			

RATINGS OF PH Series

μF	V _{DC} SV	330	V _{DC} SV	330
	350	500		350
165	16 × 27	500	25.4 × 54	
180	14.5 × 35, 18 × 29	700	30 × 54	
250	16 × 39	950	35 × 50	
260	16 × 45	1,000	35 × 50	
280	20 × 28	1,500	35 × 60	
320	22 × 40	2,000	35 × 80	
420	22 × 50			

↑
Case Size Ø D × L (mm)

Note: Case sizes are changeable upon your requests.

DIMENSIONS

Unit(mm)								
Bottom plate(Ø 25.4)								Sleeve
Ø D+0.05max.								
Safety vent(Ø 22)								L+βmax.
F±1								
Safety vent(Ø 25.4)								F±0.5
Marking : BLACK SLEEVE, SILVER INK								
Ø D	14.5	16	18	20	22	25.4	30	35
F	5.5	5.5	6	7	7	10	10	14
α	0.5	0.5	0.5	1	1	1	1	1
β	1	1	1	2	2	2	2	2