



MINIATURE ALUMINUM ELECTROLYTIC CAPACITORS

NZH Series

- 105°C 2,000Hrs assured.

- Non-solvent proof
- High ripple and High surge voltage
- For LED TV Power , SMPS
- RoHS compliant.
- Halogen-free capacitors are also available.



SPECIFICATIONS

Item	Characteristics															
Rated Voltage	450 V _{DC}															
Surge Voltage	550 V _{DC}															
Operating Temperature Range	-25 ~ +105°C															
Capacitance Tolerance	±20%(M) (at 20°C, 120Hz)															
Leakage Current	<table border="1"> <tr> <th>CV</th> <th>Time</th> <th>After 1 minute</th> <th>After 5 minutes</th> </tr> <tr> <td>≤ 1000</td> <td></td> <td>I=0.1CV+40</td> <td>I=0.03CV+15</td> </tr> <tr> <td>> 1000</td> <td></td> <td>I=0.04CV+100</td> <td>I=0.02CV+25</td> </tr> </table> <p>Where, I : Max. Leakage current(μA) C : Nominal capacitance(μF) V : Rated voltage(V_{DC}) (at 20°C)</p>				CV	Time	After 1 minute	After 5 minutes	≤ 1000		I=0.1CV+40	I=0.03CV+15	> 1000		I=0.04CV+100	I=0.02CV+25
CV	Time	After 1 minute	After 5 minutes													
≤ 1000		I=0.1CV+40	I=0.03CV+15													
> 1000		I=0.04CV+100	I=0.02CV+25													
Dissipation Factor(Tanδ)	<table border="1"> <tr> <td>Rated Voltage(V_{DC})</td> <td>450</td> </tr> <tr> <td>Tanδ(Max.)</td> <td>0.24</td> </tr> </table> <p>(at 20°C, 120Hz)</p>				Rated Voltage(V _{DC})	450	Tanδ(Max.)	0.24								
Rated Voltage(V _{DC})	450															
Tanδ(Max.)	0.24															
Temperature Characteristics (Max. Impedance ratio)	<table border="1"> <tr> <td>Rated Voltage(V_{DC})</td> <td>450</td> </tr> <tr> <td>Z(-25°C)/Z(20°C)</td> <td>6</td> </tr> </table> <p>(at 120Hz)</p>				Rated Voltage(V _{DC})	450	Z(-25°C)/Z(20°C)	6								
Rated Voltage(V _{DC})	450															
Z(-25°C)/Z(20°C)	6															
Load Life	<p>The following specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage with the rated ripple current is applied for 2,000 hours at 105°C.</p> <p>Capacitance change ≤ ±20 % of the initial value tan δ ≤ 200 % of the initial specified value Leakage current ≤ The initial specified value</p>															
Shelf Life	<p>The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours at 105°C without voltage applied. The rated voltage shall be applied to the capacitors for a minimum of 30 minutes, at least 24 hours and not more than 48 hours before the measurements.</p> <p>Capacitance change ≤ ±20 % of the initial value tan δ ≤ 200 % of the initial specified value Leakage current ≤ 500 % of the initial specified value</p>															
Others	Satisfied characteristics KS C IEC 60384-4															

DIMENSIONS OF NZH Series

Unit(mm)

				Marking : DARK BLUE SLEEVE, SILVER INK					
ØD		F		ØD	8	10	12.5	16	18
Ød	0.6	Ød	0.6	Ød	0.6	0.6	0.6	0.8	0.8
F	3.5	F	5.0	F	5.0	5.0	7.5	7.5	7.5
ØD'	ØD + 0.5 max.								
L'	L + 2.0 max								
※ Ø16 x 60L, L' ≤ L+3.0									

RATINGS OF NZH Series

Vdc	450	
Items μF	$\phi D \times L(\text{mm})$	Rated Ripple Current (mA rms/105°C, 120Hz)
18	8 X 50	240
39	10 X 50	400
47	12.5 X 40	460
	16 X 25	460
56	12.5 X 50	550
	16 X 31.5	550
	18 X 25	550
68	12.5 X 50	690
	16 X 35.5	690
	18 X 31.5	690
82	12.5 X 60	750
	16 X 40	750
	18 X 31.5	750
100	16 X 45	800
	18 X 35.5	800
120	16 X 50	950
	18 X 40	950
150	16 X 60	1,300
	18 X 50	1,300

RATED RIPPLE CURRENT MULTIPLIERS

Frequency Multipliers

Cap. (μF)\Freq.(Hz)	120	1k	10k	50k	100k
18 ~ 150	1.00	1.25	1.50	1.75	2.00