


NXW Series

• 105°C 8,000~10,000Hrs assured.

- Non-solvent proof.
- Low Impedance, High ripple
- For LED TV BLU Inverter, IP-Board, Adaptor, LED Lighting
- RoHS compliant.
- Halogen-free capacitors are also available.



SPECIFICATIONS

Item	Characteristics																							
Rated Voltage Range	6.3 ~ 50 V _{DC}																							
Operating Temperature Range	-40 ~ +105°C																							
Capacitance Tolerance	±20% (M) (at 20°C, 120Hz)																							
Leakage Current	I=0.01CV(μA) or 3μA, whichever is greater. Where, I : Max. Leakage current(μA), C : Nominal capacitance(μF), V : Rated voltage(V _{DC}) (at 20°C, 2minutes)																							
Dissipation Factor(Tanδ)	<table><tr><td>Rated voltage(V_{DC})</td><td>6.3</td><td>10</td><td>16</td><td>25</td><td>35</td><td>50</td></tr><tr><td>Tanδ(Max.)</td><td>0.22</td><td>0.19</td><td>0.16</td><td>0.14</td><td>0.12</td><td>0.10</td></tr></table> Where the capacitance exceeds 1,000μF, 0.02 shall be added every 1,000μF increase (at 20°C, 120Hz)							Rated voltage(V _{DC})	6.3	10	16	25	35	50	Tanδ(Max.)	0.22	0.19	0.16	0.14	0.12	0.10			
Rated voltage(V _{DC})	6.3	10	16	25	35	50																		
Tanδ(Max.)	0.22	0.19	0.16	0.14	0.12	0.10																		
Temperature Characteristics (Max. Impedance ratio)	<table><tr><td>Z(-25°C)/Z(+20°C)</td><td>2</td></tr><tr><td>Z(-40°C)/Z(+20°C)</td><td>3</td></tr></table> (at 120Hz)							Z(-25°C)/Z(+20°C)	2	Z(-40°C)/Z(+20°C)	3													
Z(-25°C)/Z(+20°C)	2																							
Z(-40°C)/Z(+20°C)	3																							
Load Life	The following specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage with the rated ripple current is applied (the peak voltage shall not exceed the rated voltage) at 105°C for the specified period of time. <table><tr><td>Capacitance change</td><td>≤</td><td>±30 % of the initial value</td></tr><tr><td>tan δ</td><td>≤</td><td>200 % of the initial specified value</td></tr><tr><td>Leakage current</td><td>≤</td><td>The initial specified value</td></tr></table> <table><tr><td>Case Size</td><td>Life Time</td></tr><tr><td>ø8</td><td>8,000hours</td></tr><tr><td>ø10 X 12L~12.5L</td><td>9,000hours</td></tr><tr><td>ø10 X 16L~25L ø12.5~</td><td>10,000hours</td></tr></table>							Capacitance change	≤	±30 % of the initial value	tan δ	≤	200 % of the initial specified value	Leakage current	≤	The initial specified value	Case Size	Life Time	ø8	8,000hours	ø10 X 12L~12.5L	9,000hours	ø10 X 16L~25L ø12.5~	10,000hours
Capacitance change	≤	±30 % of the initial value																						
tan δ	≤	200 % of the initial specified value																						
Leakage current	≤	The initial specified value																						
Case Size	Life Time																							
ø8	8,000hours																							
ø10 X 12L~12.5L	9,000hours																							
ø10 X 16L~25L ø12.5~	10,000hours																							
Shelf Life	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 500 hours at 105°C without voltage applied. The rated voltage shall be applied to the capacitors for a minimum of 30 minutes, at least 24 hours and not more than 48 hours before the measurements. <table><tr><td>Capacitance change</td><td>≤</td><td>±30 % of the initial value</td></tr><tr><td>tan δ</td><td>≤</td><td>200 % of the initial specified value</td></tr><tr><td>Leakage current</td><td>≤</td><td>The initial specified value</td></tr></table>							Capacitance change	≤	±30 % of the initial value	tan δ	≤	200 % of the initial specified value	Leakage current	≤	The initial specified value								
Capacitance change	≤	±30 % of the initial value																						
tan δ	≤	200 % of the initial specified value																						
Leakage current	≤	The initial specified value																						
Others	Satisfied characteristics KS C IEC 60384-4																							

DIMENSIONS OF NXW Series

Unit(mm)

Technical drawing of a capacitor showing side and end views with dimensions:

- Side View:**
 - Labels: Safety vent, Sleeve
 - Dimensions: $\phi D'$, L' , 15min. , 4min. , $\phi d \pm 0.05$
- End View (Left):**
 - Dimension: $F \pm 0.5$
 - Feature: $\leq \phi 10$
- End View (Right):**
 - Dimension: $F \pm 0.5$
 - Feature: $\geq \phi 12.5$

Marking : DARK BROWN SLEEVE, SILVER INK

ϕD	8	10	12.5	16
ϕd	0.6	0.6	0.6	0.8
F	3.5	5.0	5.0	7.5
$\phi D'$	$\phi D + 0.5 \text{ max.}$			
L'	$L + 1.5 \text{ max.}$		$L + 2.0 \text{ max.}$	

※ $\phi 10 \times 12L$, $L' \leq L + 1.5$



MINIATURE ALUMINUM ELECTROLYTIC CAPACITORS

RATINGS OF NXW Series

V _{DC} ØD×L(mm)	6.3				10				16			
	μF	IMP.		Ripple	μF	IMP.		Ripple	μF	IMP.		Ripple
		20°C	-10°C			20°C	-10°C			20°C	-10°C	
8 × 15	1,000	0.050	0.16	1,375	680	0.050	0.16	1,760	560	0.050	0.16	1,760
8 × 20	1,500	0.035	0.11	1,650	1,000	0.035	0.11	2,156	820	0.035	0.11	2,156
10 × 12	1,200	0.045	0.14	1,620	820	0.045	0.14	1,836	680	0.045	0.14	1,836
10 × 12.5	1,200	0.045	0.14	1,620	820	0.045	0.14	1,836	680	0.045	0.14	1,836
10 × 16	1,800	0.032	0.10	1,901	1,200	0.032	0.10	2,160	1,000	0.032	0.10	2,160
10 × 20	2,700	0.024	0.074	2,117	1,800	0.024	0.074	2,700	1,500	0.024	0.074	2,700
10 × 25	3,300	0.020	0.063	2,430	2,200	0.020	0.063	3,132	1,800	0.020	0.063	3,132
12.5 × 20	3,900	0.021	0.066	2,678	2,700	0.021	0.066	2,808	2,200	0.021	0.066	2,808
12.5 × 25	4,700	0.016	0.050	3,132	3,300	0.016	0.050	3,294	2,700	0.016	0.050	3,294
12.5 × 30	5,600	0.015	0.047	3,726	4,700	0.015	0.047	3,780	3,300	0.015	0.047	3,780
12.5 × 35	6,800	0.014	0.042	3,856	5,600	0.014	0.042	3,888	3,900	0.014	0.042	3,888
16 × 20	6,800	0.018	0.055	3,413	4,700	0.018	0.055	3,413	3,300	0.018	0.055	3,413
16 × 25	8,200	0.014	0.045	3,812	5,600	0.014	0.045	3,812	4,700	0.014	0.045	3,812

V _{DC} ØD×L(mm)	25				35				50			
	μF	IMP.		Ripple	μF	IMP.		Ripple	μF	IMP.		Ripple
		20°C	-10°C			20°C	-10°C			20°C	-10°C	
8 × 15	390	0.050	0.16	1,760	220	0.050	0.16	1,760	120	0.074	0.24	1,353
8 × 20	560	0.035	0.11	2,156	330	0.035	0.11	2,156	180	0.053	0.17	1,738
10 × 12	470	0.045	0.14	1,836	270	0.045	0.14	1,836	150	0.062	0.19	1,382
10 × 12.5	470	0.045	0.14	1,836	270	0.045	0.14	1,836	150	0.062	0.19	1,382
10 × 16	680	0.032	0.10	2,160	390	0.032	0.10	2,160	220	0.045	0.14	1,782
10 × 20	1,000	0.024	0.074	2,700	560	0.024	0.074	2,700	330	0.032	0.10	2,305
10 × 25	1,200	0.020	0.063	3,132	680	0.020	0.063	3,132	390	0.027	0.08	2,419
12.5 × 20	1,500	0.021	0.066	2,808	820	0.021	0.066	2,808	470	0.027	0.08	2,376
12.5 × 25	1,800	0.016	0.050	3,294	1,200	0.016	0.050	3,294	680	0.021	0.066	2,700
12.5 × 30	2,200	0.015	0.047	3,780	1,500	0.015	0.047	3,780	820	0.020	0.061	3,348
12.5 × 35	2,700	0.014	0.042	3,888	1,800	0.014	0.042	3,888	1,000	0.018	0.055	3,510
16 × 20	2,200	0.018	0.055	3,413	1,500	0.018	0.055	3,413	820	0.022	0.069	2,867
16 × 25	3,300	0.014	0.045	3,812	1,800	0.014	0.045	3,812	1,000	0.019	0.058	3,161

↑ Rated Ripple Current (mA rms/105°C, 100kHz)
↑ Impedance (Ω max./100kHz)
↑ Nominal Capacitance(μF)

RATED RIPPLE CURRENT MULTIPLIERS

Frequency Multipliers

Freq.(Hz) Cap.(μF)	120	1k	10k	50k	100k
120~270	0.50	0.73	0.92	0.95	1.00
330~680	0.55	0.77	0.94	0.96	1.00
820~1,800	0.60	0.80	0.96	0.97	1.00
2,200~8,200	0.70	0.85	0.98	0.99	1.00