

BXJ Series

• 105°C 2,000~5,000Hrs assured.

- Vertical SMD type.
- Very low Impedance, Long Life.
- For STB, Tuner.
- RoHS compliant.
- Halogen-free capacitors are also available.

• AEC-Q200 compliant : Please contact us for more details, test data, information.

Solvent-proof

WV ≤ 63V_{DC}

BXE

Long Life

BXJ



SPECIFICATIONS

Item	Characteristics								
Rated Voltage Range	6.3 ~ 50V _{DC}					63 ~ 100V _{DC}			
Operating Temperature Range	-55 ~ +105℃					-40 ~ +105℃			
Capacitance Tolerance	±20%(M) (at 20℃, 120Hz)								
Leakage Current	I=0.01CV(μA) or 3μA, whichever is greater. Where, I:Max. Leakage current(μA), C:Nominal capacitance(μF), V:Rated voltage(V _{DC}) (at 20℃, 2 minutes)								
Dissipation Factor(Tanδ)	Rated Voltage(V _{DC})	6.3	10	16	25	35	50	63	100
	Tanδ (Max.)	0.26	0.19	0.16	0.14	0.12	0.12	0.12	0.12
Temperature Characteristics (Max. Impedance ratio)	(at 20℃, 120Hz)								
	Rated voltage(V _{DC})	6.3	10	16	25	35	50	63	100
	Z(-25℃)/Z(+20℃)	3	2	2	2	2	2	3	3
	Z(-55℃)/Z(+20℃)	5	4	4	3	3	3	※4	※4
	※Z(-40℃)/Z(+20℃) (at 120Hz)								
Load Life	The following specifications shall be satisfied when the capacitors are restored to 20℃ after the rated voltage is applied with the following conditions. D56~H63, J85 : 105℃, 2,000 hours, H10 ~ K14 : 105℃, 5,000 hours. Capacitance change D56~H63, J85 ≤ ±30% of the initial value H10~K14 ≤ ±35% of the initial value Tanδ ≤ 300% of the initial specified value Leakage current ≤ The initial specified value								
Shelf Life	The following specifications shall be satisfied when the capacitors are restored to 20℃ after exposing them for 1,000 hours at 105℃ without voltage applied. The rated voltage shall be applied to the capacitors for a minimum of 30 minutes, at least 24 hours and not more than 48 hours before the measurements. Capacitance change D56~H63, J85 ≤ ±30% of the initial value H10~K14 ≤ ±35% of the initial value Tanδ ≤ 300% of the initial specified value Leakage current ≤ The initial specified value								
Others	Satisfied characteristics KS C IEC 60384-4								

PART NUMBERING SYSTEM

BXJ	6.3	VC	220	M	F60	TP
						With tape
						Case code
						Capacitance tolerance(±20%)
						Nominal capacitance code (ex. 0.1μF:R1, 1.0μF:1, 4.7μF:4R7, 10μF:10)
						Lead type
						Rated voltage
						Series name

RATED RIPPLE CURRENT MULTIPLIERS

Frequency Multipliers

Size code	Cap.(μF)	Freq.(Hz)	120	1K	10K	100K
D56 ~ J10	4.7		0.35	0.70	0.90	1.00
	10 ~ 100		0.40	0.75	0.90	1.00
	220 ~ 470		0.50	0.85	0.94	1.00
	1,000 ~ 1,500		0.60	0.87	0.95	1.00
K14	47 ~ 100		0.40	0.75	0.90	1.00
	330 ~ 470		0.50	0.85	0.94	1.00
	680 ~ 2,000		0.60	0.87	0.95	1.00

DIMENSIONS OF BXJ Series

Unit(mm)

DIMENSIONS

● Vibration Resistance

〈Size code:D56~K14〉 〈Size code:H10~K14〉

■ : Dummy terminals

Recommended solder land on PC board

■ : Solder land on PC board

MARKING

〈D56 ~ J10〉 〈K14〉

Note 1 : L±0.5 for 8×6.3(H63)~12.5×13.5(K14)
 Note 2 : 4×5.3(D56), 5×5.3(E56), 5×5.8(E61) is excluded symbol mark.
 Note 3 : 6.3WV is marked by 6V.

Case code	∅D	L	A	B	C	W	P	a	b	c	a	b	c
D56	4	5.3	4.3	4.3	5.1	0.5~0.8	1.0	1.0	2.6	1.6			
E56	5	5.3	5.3	5.3	5.9	0.5~0.8	1.4	1.4	3.0	1.6			
E61	5	5.8	5.3	5.3	5.9	0.5~0.8	1.4	1.4	3.0	1.6			
F55	6.3	5.2	6.6	6.6	7.2	0.5~0.8	1.9	1.9	3.5	1.6			
F60	6.3	5.7	6.6	6.6	7.2	0.5~0.8	1.9	1.9	3.5	1.6			
F80	6.3	7.7	6.6	6.6	7.2	0.5~0.8	1.9	1.9	3.5	1.6			
H63	8	6.3	8.3	8.3	9.0	0.5~0.8	2.3	2.3	4.5	1.6			
H10	8	10	8.3	8.3	9.0	0.7~1.1	3.1	3.1	4.2	2.2	3.1	4.2	3.5
J85	10	8.5	10.3	10.3	11.0	0.7~1.1	4.5	4.5	4.4	2.2			
J10	10	10	10.3	10.3	11.0	0.7~1.1	4.5	4.5	4.4	2.2	4.5	4.4	3.5
K14	12.5	13.5	13.0	13.0	13.7	1.0~1.3	4.2	4.0	5.7	2.5	3.4	6.3	9.3

● Vibration Resistance

RATINGS OF BXJ Series

μF \ V _{DC}	6.3			10			16			25			35			50			63			100		
4.7													D56	1.80	85	E56	3.00	55						
10							D56	1.80	85	D56	1.80	85	D56	1.80	85	E61	2.00	50	F60	4.50	48	H63	1.80	85
													E56	0.80	155	F60	1.20	120						
22				D56	1.80	85	E56	0.80	155	E56	0.80	155	E61	0.70	160	F60	1.20	120	H63	1.50	100	H10	1.50	160
							E61	0.70	160	E61	0.70	160	F55	0.55	220				H10	1.00	200			
33	D56	1.80	85	E56	0.80	155	F60	0.36	240	F60	0.36	240	F60	0.36	240	F80	0.90	150	J85	0.95	205	J10	0.60	330
							E61	0.70	160	F55	0.55	220												
47	E56	0.80	155	E61	0.70	160	F60	0.36	240	F60	0.36	240	F60	0.36	240	H63	0.75	200	H10	1.00	200	K14	0.40	400
				F60	0.36	240																		
68	E61	0.70	160	E61	0.70	160	F60	0.36	240	F60	0.36	240	F80	0.34	280	H10	0.44	300	J10	0.50	350	K14	0.40	400
	F60	0.36	240	F60	0.36	240				F80	0.34	280	H63	0.26	300									
100	E61	0.70	160	F60	0.36	240	F60	0.36	240	H63	0.26	300	H10	0.16	600	H10	0.44	300	J10	0.50	350	K14	0.40	400
	F60	0.36	240										H10	0.16	600	J85	0.15	620						
220	F60	0.36	240	F80	0.34	280	F80	0.34	280	J85	0.15	620	H10	0.16	600	H10	0.16	600	J10	0.25	500			
							H10	0.16	600	H10	0.16	600												
330	F80	0.34	280	H10	0.16	600	J85	0.15	620	J10	0.08	850	J10	0.08	850	K14	0.11	650						
							H10	0.16	600															
470	H10	0.16	600	H10	0.16	600	J10	0.08	850	J10	0.08	850	K14	0.06	1,100									
	J85	0.15	620	J85	0.15	620																		
1,000	H10	0.16	600	J10	0.08	850	K14	0.06	1,100	K14	0.06	1,100												
1,500	J10	0.08	850	K14	0.06	1,100																		
2,200	K14	0.06	1,100	K14	0.06	1,100																		

↑ Rated Ripple Current (mA rms/105°C, 100kHz)
 ↑ Impedance (Ω max./20°C, 100kHz)
 ↑ Case code