


NLA Series

• 105°C 4,000~10,000Hrs assured.

Solvent-proof

- Low impedance.
- Long Life.
- For SMPS, IP-Board, Adaptor
- RoHS compliant.
- Halogen-free capacitors are also available.



SPECIFICATIONS

Item	Characteristics																					
Rated Voltage Range	6.3 ~ 50 V _{DC}																					
Operating Temperature Range	-55 ~ +105°C																					
Capacitance Tolerance	±20%(M) (at 20°C, 120Hz)																					
Leakage Current	I=0.01CV or 3µA, whichever is greater. Where, I: Max.Leakage current(µA) C: Nominal capacitance (µF) V: Rated voltage (V _{DC}) (at 20°C, 2 minutes)																					
Dissipation Factor (Tanδ)	<table border="1"> <tr> <td>Rated Voltage(V_{DC})</td> <td>6.3</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> </tr> <tr> <td>Tanδ(Max.)</td> <td>0.22</td> <td>0.19</td> <td>0.16</td> <td>0.14</td> <td>0.12</td> <td>0.10</td> </tr> </table> <p>(at 20°C, 120Hz) When the capacitance exceeds 1,000µF, 0.02 shall be added every 1,000µF increase.</p>	Rated Voltage(V _{DC})	6.3	10	16	25	35	50	Tanδ(Max.)	0.22	0.19	0.16	0.14	0.12	0.10							
Rated Voltage(V _{DC})	6.3	10	16	25	35	50																
Tanδ(Max.)	0.22	0.19	0.16	0.14	0.12	0.10																
Temperature Characteristics (Max. Impedance ratio)	<table border="1"> <tr> <td>Rated voltage(V_{DC})</td> <td>6.3</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> </tr> <tr> <td>Z(-25°C)/Z(+20°C)</td> <td>4</td> <td>3</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> </tr> <tr> <td>Z(-40°C)/Z(+20°C)</td> <td>8</td> <td>6</td> <td>4</td> <td>3</td> <td>3</td> <td>4</td> </tr> </table> <p>(at 120Hz)</p>	Rated voltage(V _{DC})	6.3	10	16	25	35	50	Z(-25°C)/Z(+20°C)	4	3	2	2	2	2	Z(-40°C)/Z(+20°C)	8	6	4	3	3	4
Rated voltage(V _{DC})	6.3	10	16	25	35	50																
Z(-25°C)/Z(+20°C)	4	3	2	2	2	2																
Z(-40°C)/Z(+20°C)	8	6	4	3	3	4																
Load Life	<p>The following specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage is applied at 105°C for the following test time.</p> <table border="1"> <tr> <td>Capacitance change</td> <td>≤ ±25% of the initial value</td> </tr> <tr> <td>Tanδ</td> <td>≤ 200% of the initial specified value</td> </tr> <tr> <td>Leakage current</td> <td>≤ The initial specified value</td> </tr> </table> <table border="1"> <tr> <td>∅ D</td> <td>6.3~10V</td> <td>16~50V</td> </tr> <tr> <td>∅ 5~6.3</td> <td>4,000 hours</td> <td>5,000 hours</td> </tr> <tr> <td>∅ 8~10</td> <td>6,000 hours</td> <td>7,000 hours</td> </tr> <tr> <td>∅ 12.5~</td> <td>8,000 hours</td> <td>10,000 hours</td> </tr> </table>	Capacitance change	≤ ±25% of the initial value	Tanδ	≤ 200% of the initial specified value	Leakage current	≤ The initial specified value	∅ D	6.3~10V	16~50V	∅ 5~6.3	4,000 hours	5,000 hours	∅ 8~10	6,000 hours	7,000 hours	∅ 12.5~	8,000 hours	10,000 hours			
Capacitance change	≤ ±25% of the initial value																					
Tanδ	≤ 200% of the initial specified value																					
Leakage current	≤ The initial specified value																					
∅ D	6.3~10V	16~50V																				
∅ 5~6.3	4,000 hours	5,000 hours																				
∅ 8~10	6,000 hours	7,000 hours																				
∅ 12.5~	8,000 hours	10,000 hours																				
Shelf Life	<p>The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours at 105°C without voltage applied. The rated voltage shall be applied to the capacitors for a minimum of 30 minutes, at least 24 hours and not more than 48 hours before the measurements.</p> <p>Capacitance change ≤ ±25% of the initial value Tanδ ≤ 200% of the initial specified value Leakage current ≤ The initial specified value</p>																					
Others	Satisfied characteristics KS C IEC 60384-4																					

DIMENSIONS OF NLA Series

Unit (mm)

Marking : DARK BROWN SLEEVE, GOLD INK

∅D	5	6.3	8	10	12.5	16	18
∅d	0.5	0.5	0.6	0.6	0.6	0.8	0.8
F	2.0	2.5	3.5	5.0	5.0	7.5	7.5
∅D'	∅D + 0.5 max.						
L'	L + 1.5 max.			L + 2.0 max.			



MINIATURE ALUMINUM ELECTROLYTIC CAPACITORS

RATINGS OF NLA Series

∅ D x L (mm) \ Vdc	6.3			10			16		
	μF	IMP.	Ripple	μF	IMP.	Ripple	μF	IMP.	Ripple
5 x 11	150	0.50	175	100	0.50	175	47	0.50	175
6.3 x 11	330	0.25	290	220	0.25	290	100	0.25	290
8 x 11.5	680	0.12	555	470	0.12	555	330	0.12	555
8 x 15	1,000	0.090	730	680	0.090	730	470	0.090	730
8 x 20	1,200	0.080	810	1,000	0.080	810	560	0.080	810
10 x 12.5	820	0.090	760	680	0.090	760	470	0.090	760
10 x 16	1,200	0.068	1,050	1,000	0.068	1,050	680	0.068	1,050
10 x 20	1,500	0.052	1,220	1,200	0.052	1,220	1,000	0.052	1,220
10 x 25	2,200	0.045	1,440	1,500	0.045	1,440	1,200	0.045	1,440
10 x 30	2,700	0.037	1,690	1,800	0.037	1,690	1,500	0.037	1,690
12.5 x 16	1,800	0.053	1,270	1,500	0.053	1,270	1,000	0.053	1,270
12.5 x 20	3,300	0.038	1,660	2,200	0.038	1,660	1,500	0.038	1,660
12.5 x 25	3,900	0.030	2,310	3,300	0.030	2,310	2,200	0.030	2,310
12.5 x 30	4,700	0.025	2,510	3,900	0.025	2,510	2,700	0.025	2,510
12.5 x 35	5,600	0.022	2,870	4,700	0.022	2,870	3,300	0.022	2,870
16 x 15	2,700	0.048	1,690	2,200	0.048	1,690	1,500	0.048	1,690
16 x 20	5,600	0.031	2,210	3,900	0.031	2,210	2,700	0.031	2,210
16 x 25	6,800	0.024	2,560	5,600	0.024	2,560	3,900	0.024	2,560
16 x 31.5	8,200	0.021	3,010	6,800	0.021	3,010	4,700	0.021	3,010
16 x 35	10,000	0.019	3,250	8,200	0.019	3,250	5,600	0.019	3,250
16 x 40	12,000	0.016	3,560	10,000	0.016	3,560	6,800	0.016	3,560
18 x 15	3,900	0.051	1,920	2,700	0.051	1,920	2,200	0.051	1,920
18 x 20	6,800	0.031	2,490	5,600	0.031	2,490	3,900	0.031	2,490
18 x 25	10,000	0.023	2,740	6,800	0.023	2,740	4,700	0.023	2,740
18 x 31.5	12,000	0.021	3,330	8,200	0.021	3,330	5,600	0.021	3,330
18 x 35.5	15,000	0.019	3,680	10,000	0.019	3,680	8,200	0.019	3,680
18 x 40	18,000	0.018	3,800	12,000	0.018	3,800	10,000	0.018	4,280

∅ D x L (mm) \ Vdc	25			35			50		
	μF	IMP.	Ripple	μF	IMP.	Ripple	μF	IMP.	Ripple
5 x 11	47	0.50	175	33	0.50	175	10	2.0	100
6.3 x 11	100	0.25	290	56	0.25	290	22	1.6	150
8 x 11.5	220	0.12	555	150	0.12	555	47	0.80	180
8 x 15	330	0.090	730	220	0.090	730	100	0.50	230
8 x 20	390	0.080	810	270	0.080	810	120	0.30	360
10 x 12.5	330	0.090	760	220	0.090	760	100	0.28	380
10 x 16	470	0.068	1,050	330	0.068	1,050	150	0.19	525
10 x 20	680	0.052	1,220	470	0.052	1,220	220	0.14	610
10 x 25	820	0.045	1,440	560	0.045	1,440	270	0.11	720
10 x 30	1,000	0.037	1,690	680	0.037	1,690	330	0.091	845
12.5 x 16	680	0.053	1,270	470	0.053	1,270	220	0.15	630
12.5 x 20	1,000	0.038	1,660	680	0.038	1,660	330	0.098	830
12.5 x 25	1,500	0.030	2,310	1,000	0.030	2,310	470	0.074	975
12.5 x 30	1,800	0.025	2,510	1,200	0.025	2,510	680	0.062	1,150
12.5 x 35	2,200	0.022	2,870	1,500	0.022	2,870	820	0.052	1,250
16 x 15	1,000	0.048	1,690	680	0.048	1,690	390	0.11	845
16 x 20	1,800	0.031	2,210	1,200	0.031	2,210	680	0.070	1,100
16 x 25	2,700	0.024	2,560	1,800	0.024	2,560	820	0.052	1,280
16 x 31.5	3,300	0.021	3,010	2,200	0.021	3,010	1,000	0.045	1,500
16 x 35	3,900	0.019	3,250	2,700	0.019	3,250	1,200	0.039	1,680
16 x 40	4,700	0.016	3,560	3,300	0.016	3,560	1,500	0.033	1,850
18 x 15	1,200	0.051	1,920	1,000	0.051	1,920	390	0.11	965
18 x 20	2,200	0.031	2,490	1,800	0.031	2,490	680	0.074	1,250
18 x 25	3,300	0.023	2,740	2,200	0.023	2,740	1,000	0.054	1,370
18 x 31.5	3,900	0.021	3,330	2,700	0.021	3,330	1,200	0.043	1,810
18 x 35.5	4,700	0.019	3,680	3,300	0.019	3,680	1,500	0.035	1,850
18 x 40	5,600	0.012	4,280	3,900	0.012	4,280	1,800	0.029	1,900

RATED RIPPLE CURRENT MULTIPLIERS

Cap. (μF) \ Freq. (Hz)	120	1k	10k	100k
~ 180	0.40	0.75	0.90	1.0
220 ~ 560	0.50	0.85	0.94	1.0
680 ~ 1,800	0.60	0.87	0.95	1.0
2,200 ~ 3,900	0.75	0.90	0.95	1.0
4,700 ~ 18,000	0.85	0.95	0.98	1.0

