

NZE Series

• 105°C 2,000Hrs assured.

- Non-solvent proof.
- Downsized, High Ripple.
- For SMPS, IP-Board, Adaptor.
- RoHS compliant.
- Halogen-free capacitors are also available.

NFD
(KMF)

NZE

Downsized



SPECIFICATIONS

| Item | Characteristics | | | | | | | | | | | | | |
|---|--|---------------------------|---------------------------------|----------------|-----------------|------------|-------------------|-----------------|--------|------------------|-------------------|---|---|---|
| Rated Voltage Range | 160 ~ 400 V _{DC} | 420 ~ 500 V _{DC} | | | | | | | | | | | | |
| Operating Temperature Range | -40 ~ + 105°C | -25 ~ + 105°C | | | | | | | | | | | | |
| Capacitance Tolerance | ±20%(M) (at 20°C, 120Hz) | | | | | | | | | | | | | |
| Leakage Current | <table border="1"> <thead> <tr> <th>C · V \ Time</th> <th>After 1 minute</th> <th>After 5 minutes</th> </tr> </thead> <tbody> <tr> <td>≤ 1000</td> <td>I = 0.1CV + 40</td> <td>I = 0.03CV + 15</td> </tr> <tr> <td>> 1000</td> <td>I = 0.04CV + 100</td> <td>I = 0.02CV + 25</td> </tr> </tbody> </table> <p>Where, I:Max. Leakage current(μA) C:Nominal capacitance(μF) V:Rated voltage(V_{DC}) (at 20°C)</p> | | C · V \ Time | After 1 minute | After 5 minutes | ≤ 1000 | I = 0.1CV + 40 | I = 0.03CV + 15 | > 1000 | I = 0.04CV + 100 | I = 0.02CV + 25 | | | |
| C · V \ Time | After 1 minute | After 5 minutes | | | | | | | | | | | | |
| ≤ 1000 | I = 0.1CV + 40 | I = 0.03CV + 15 | | | | | | | | | | | | |
| > 1000 | I = 0.04CV + 100 | I = 0.02CV + 25 | | | | | | | | | | | | |
| Dissipation Factor(Tanδ) | <table border="1"> <thead> <tr> <th>Rated Voltage(V_{DC})</th> <th>160~250</th> <th>350~500</th> </tr> </thead> <tbody> <tr> <td>Tanδ(Max.)</td> <td>0.20</td> <td>0.24</td> </tr> </tbody> </table> <p>(at 20°C, 120Hz)</p> | | Rated Voltage(V _{DC}) | 160~250 | 350~500 | Tanδ(Max.) | 0.20 | 0.24 | | | | | | |
| Rated Voltage(V _{DC}) | 160~250 | 350~500 | | | | | | | | | | | | |
| Tanδ(Max.) | 0.20 | 0.24 | | | | | | | | | | | | |
| Temperature Characteristics (Max. Impedance ratio) | <table border="1"> <thead> <tr> <th>Rated Voltage(V_{DC})</th> <th>160~250</th> <th>350~400</th> <th>420~500</th> </tr> </thead> <tbody> <tr> <td>Z(-25°C)/Z(+20°C)</td> <td>3</td> <td>5</td> <td>6</td> </tr> <tr> <td>Z(-40°C)/Z(+20°C)</td> <td>6</td> <td>6</td> <td>—</td> </tr> </tbody> </table> <p>(at 120Hz)</p> | | Rated Voltage(V _{DC}) | 160~250 | 350~400 | 420~500 | Z(-25°C)/Z(+20°C) | 3 | 5 | 6 | Z(-40°C)/Z(+20°C) | 6 | 6 | — |
| Rated Voltage(V _{DC}) | 160~250 | 350~400 | 420~500 | | | | | | | | | | | |
| Z(-25°C)/Z(+20°C) | 3 | 5 | 6 | | | | | | | | | | | |
| Z(-40°C)/Z(+20°C) | 6 | 6 | — | | | | | | | | | | | |
| Load Life | <p>The following specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage with the rated ripple current is applied (the peak voltage shall not exceed the rated voltage)for 2,000 hours at 105°C.</p> <p>Capacitance change ≤ ±20% of the initial value Tanδ ≤ 200% of the initial specified value Leakage current ≤ The initial specified value</p> | | | | | | | | | | | | | |
| Shelf Life | <p>The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours at 105°C without voltage applied. The rated voltage shall be applied to the capacitors for a minimum of 30 minutes, at least 24 hours and not more than 48 hours before the measurements.</p> <p>Capacitance change ≤ ±20% of the initial value Tanδ ≤ 200% of the initial specified value Leakage current ≤ 500% of the initial specified value</p> | | | | | | | | | | | | | |
| Others | Satisfied characteristics KS C IEC 60384-4 | | | | | | | | | | | | | |

DIMENSIONS OF NZE Series

Unit(mm)

Marking : DARK BROWN SLEEVE, SILVER INK

| | 6.3 | 8 | 10 | 12.5 | 16 | 18 | 20 | 22 | 25.4 |
|-----|---------------|-----|-----|--------------|-----|-----|-----|------|------|
| øD | 6.3 | 8 | 10 | 12.5 | 16 | 18 | 20 | 22 | 25.4 |
| ød | 0.5 | 0.6 | 0.6 | 0.6 | 0.8 | 0.8 | 0.8 | 1.0 | 1.0 |
| F | 2.5 | 3.5 | 5.0 | 5.0 | 7.5 | 7.5 | 7.5 | 10.0 | 10.0 |
| øD' | øD + 0.5 max. | | | | | | | | |
| L' | L + 1.5max. | | | L + 2.0 max. | | | | | |

RATINGS OF NZE Series

| V _{dc} | Capacitance (μF) | ∅D×L(mm) | Rated Ripple Current (mA _{rms} /105°C, 120Hz) |
|-----------------|------------------|-----------|--|
| 160 | 22 | 10 × 20 | 211 |
| | 33 | 10 × 20 | 260 |
| | 47 | 10 × 25 | 338 |
| | 68 | 12.5 × 20 | 413 |
| | 82 | 12.5 × 25 | 494 |
| | 100 | 12.5 × 30 | 589 |
| | 120 | 16 × 20 | 615 |
| | 150 | 12.5 × 35 | 710 |
| | | 16 × 25 | 738 |
| | 180 | 16 × 25 | 809 |
| | 220 | 16 × 31.5 | 964 |
| | 270 | 16 × 35.5 | 1091 |
| | 330 | 18 × 31.5 | 1221 |
| | | 22 × 25 | 1230 |
| | 390 | 18 × 35.5 | 1371 |
| | | 22 × 30 | 1410 |
| | 470 | 25.4 × 30 | 1660 |
| | 560 | 22 × 35 | 1780 |
| | | 22 × 40 | 1870 |
| | 680 | 22 × 45 | 2150 |
| 25.4 × 35 | | 2100 | |
| 820 | 22 × 50 | 2450 | |
| | 25.4 × 40 | 2420 | |
| 1000 | 25.4 × 50 | 2880 | |
| 200 | 3.3 | 6.3 × 11 | 45 |
| | 4.7 | 8 × 11.5 | 64 |
| | 6.8 | 8 × 11.5 | 77 |
| | 10 | 8 × 11.5 | 94 |
| | 22 | 8 × 20 | 160 |
| | 33 | 10 × 20 | 260 |
| | 47 | 10 × 25 | 338 |
| | 68 | 12.5 × 25 | 413 |
| | 82 | 12.5 × 25 | 494 |
| | 100 | 12.5 × 30 | 589 |
| | 120 | 16 × 25 | 660 |
| | 150 | 16 × 25 | 738 |
| | 180 | 16 × 31.5 | 872 |
| | 220 | 16 × 31.5 | 964 |
| | | 22 × 25 | 1030 |
| | 270 | 16 × 35.5 | 1091 |
| | | 18 × 31.5 | 1104 |
| | 330 | 16 × 40 | 1245 |
| | | 18 × 35.5 | 1261 |
| | | 22 × 30 | 1290 |
| | | 25.4 × 30 | 1280 |
| | 390 | 18 × 40 | 1393 |
| | | 22 × 35 | 1370 |
| | 470 | 22 × 40 | 1580 |
| | | 25.4 × 35 | 1610 |
| | 560 | 22 × 45 | 1790 |
| | | 22 × 50 | 1860 |
| | | 25.4 × 40 | 1840 |
| | 820 | 25.4 × 50 | 2400 |

| V _{dc} | Capacitance (μF) | ∅D×L(mm) | Rated Ripple Current (mA _{rms} /105°C, 120Hz) |
|-----------------|------------------|-----------|--|
| 250 | 4.7 | 8 × 11.5 | 72 |
| | 6.8 | 8 × 11.5 | 86 |
| | 10 | 8 × 15 | 108 |
| | 22 | 10 × 20 | 211 |
| | 33 | 10 × 25 | 284 |
| | 47 | 12.5 × 20 | 343 |
| | 68 | 12.5 × 30 | 488 |
| | 82 | 16 × 25 | 546 |
| | 100 | 16 × 25 | 603 |
| | 120 | 16 × 25 | 660 |
| | 150 | 16 × 31.5 | 796 |
| | 180 | 16 × 35.5 | 891 |
| | | 18 × 31.5 | 901 |
| | | 22 × 25 | 830 |
| | 220 | 16 × 40 | 1016 |
| | | 18 × 35.5 | 1030 |
| | | 22 × 30 | 1050 |
| | 270 | 18 × 40 | 1158 |
| | | 22 × 35 | 1140 |
| | | 25.4 × 30 | 1160 |
| 330 | 18 × 45 | 1267 | |
| | 22 × 40 | 1320 | |
| | 25.4 × 35 | 1350 | |
| 390 | 22 × 45 | 1500 | |
| | 25.4 × 40 | 1530 | |
| 470 | 22 × 50 | 1710 | |
| 560 | 25.4 × 50 | 1990 | |
| 350 | 10 | 10 × 16 | 118 |
| | 15 | 10 × 20 | 169 |
| | 22 | 10 × 25 | 228 |
| | 33 | 12.5 × 25 | 304 |
| | 39 | 10 × 40 | 374 |
| | 47 | 16 × 25 | 400 |
| | 56 | 16 × 25 | 437 |
| | 68 | 16 × 31.5 | 510 |
| | | 18 × 25 | 502 |
| | 82 | 16 × 35.5 | 582 |
| | | 18 × 31.5 | 590 |
| | 100 | 18 × 31.5 | 632 |
| | | 22 × 25 | 630 |
| | 120 | 18 × 35.5 | 716 |
| | | 22 × 30 | 730 |
| | 150 | 25.4 × 30 | 880 |
| | 180 | 22 × 35 | 950 |
| | 200 | 22 × 40 | 1050 |
| | | 25.4 × 35 | 1070 |
| | 220 | 22 × 45 | 1150 |
| 270 | 22 × 50 | 1320 | |
| | 25.4 × 40 | 1300 | |
| 330 | 25.4 × 50 | 1560 | |

RATED RIPPLE CURRENT MULTIPLIERS

Frequency Multipliers

| Freq.(Hz) | 120 | 1K | 10K | 50K | 100K |
|-----------|------|------|------|------|------|
| Factor | 1.00 | 1.25 | 1.50 | 1.60 | 1.75 |

RATINGS OF NZE Series

| V _{dc} | Capacitance (μF) | ∅ D×L(mm) | Rated Ripple Current (mA _{rms} /105°C, 120Hz) |
|-----------------|------------------|-----------|--|
| 400 | 4.7 | 6.3 × 15 | 55 |
| | 6.8 | 8 × 11 | 101 |
| | | 8 × 15 | 102 |
| | 8.2 | 8 × 15 | 105 |
| | | 8 × 20 | 110 |
| | 10 | 8 × 20 | 115 |
| | | 10 × 16 | 118 |
| | 15 | 10 × 20 | 169 |
| | 22 | 10 × 25 | 228 |
| | 33 | 12.5 × 25 | 304 |
| | 39 | 12.5 × 30 | 355 |
| | 47 | 16 × 25 | 400 |
| | 56 | 16 × 25 | 437 |
| | 68 | 16 × 31.5 | 510 |
| | 82 | 16 × 35.5 | 582 |
| | | 18 × 31.5 | 590 |
| | | 22 × 25 | 590 |
| | 100 | 16 × 40 | 645 |
| | | 18 × 35.5 | 786 |
| | 120 | 18 × 40 | 801 |
| | | 22 × 30 | 790 |
| | 150 | 18 × 40 | 872 |
| | | 22 × 35 | 900 |
| 25.4 × 30 | | 920 | |
| 180 | 22 × 40 | 1040 | |
| | 25.4 × 35 | 1060 | |
| 200 | 22 × 45 | 1140 | |
| 220 | 22 × 50 | 1250 | |
| | 25.4 × 40 | 1110 | |
| 270 | 25.4 × 50 | 1400 | |
| 330 | 25.4 × 50 | 1450 | |
| 420 | 10 | 10 × 20 | 129 |
| | 15 | 12.5 × 16 | 161 |
| | 22 | 12.5 × 20 | 207 |
| | 33 | 16 × 20 | 265 |
| | 47 | 16 × 25 | 374 |
| | 56 | 16 × 31.5 | 440 |
| | 68 | 18 × 25 | 492 |
| | | 18 × 31.5 | 520 |
| | 82 | 18 × 31.5 | 640 |
| | | 22 × 25 | 550 |
| | 100 | 16 × 45 | 750 |
| | | 18 × 35.5 | 750 |
| | | 22 × 30 | 650 |
| | 120 | 16 × 45 | 780 |
| | | 18 × 40 | 819 |
| | | 22 × 35 | 750 |
| | 150 | 25.4 × 30 | 760 |
| | | 18 × 45 | 840 |
| | | 20 × 40 | 845 |
| | | 22 × 40 | 880 |
| | 180 | 25.4 × 35 | 890 |
| | | 22 × 45 | 1000 |
| | 200 | 25.4 × 40 | 1080 |
| 220 | 22 × 50 | 1150 | |
| 270 | 25.4 × 50 | 1360 | |

| V _{dc} | Capacitance (μF) | ∅ D×L(mm) | Rated Ripple Current (mA _{rms} /105°C, 120Hz) |
|-----------------|------------------|-----------|--|
| 450 | 4.7 | 8 × 20 | 80 |
| | 8.2 | 10 × 16 | 108 |
| | 10 | 10 × 20 | 129 |
| | 15 | 12.5 × 20 | 173 |
| | 22 | 12.5 × 25 | 232 |
| | 33 | 12.5 × 30 | 292 |
| | | 16 × 25 | 306 |
| | 39 | 10 × 45 | 330 |
| | 47 | 16 × 25 | 374 |
| | 53 | 10 × 50 | 424 |
| | 56 | 16 × 31.5 | 440 |
| | 68 | 16 × 35.5 | 514 |
| | | 18 × 31.5 | 520 |
| | | 22 × 25 | 500 |
| | 82 | 12.5 × 50 | 670 |
| | | 16 × 40 | 640 |
| | | 18 × 31.5 | 640 |
| | 100 | 12.5 × 60 | 790 |
| | | 16 × 45 | 750 |
| | | 18 × 35.5 | 750 |
| | 120 | 22 × 30 | 740 |
| | | 16 × 50 | 819 |
| | | 18 × 40 | 819 |
| 22 × 35 | | 750 | |
| 150 | 25.4 × 30 | 760 | |
| | 18 × 45 | 840 | |
| | 20 × 40 | 845 | |
| | 22 × 40 | 880 | |
| 180 | 25.4 × 35 | 890 | |
| | 22 × 45 | 1000 | |
| | 25.4 × 40 | 1030 | |
| 200 | 22 × 50 | 1100 | |
| 220 | 25.4 × 50 | 1230 | |
| 500 | 22 | 12.5 × 30 | 238 |
| | 33 | 12.5 × 45 | 327 |
| | 39 | 12.5 × 50 | 376 |
| | 47 | 16 × 35.5 | 385 |
| | | 18 × 31.5 | 389 |
| | 56 | 12.5 × 60 | 473 |
| | | 16 × 40 | 452 |
| | | 22 × 25 | 450 |
| | 60 | 12.5 × 60 | 494 |
| | 68 | 16 × 45 | 567 |
| | | 18 × 35.5 | 546 |
| | | 22 × 30 | 530 |
| | 82 | 16 × 50 | 599 |
| | | 18 × 40 | 588 |
| | | 25.4 × 30 | 620 |
| | | 18 × 45 | 700 |
| | 100 | 20 × 40 | 700 |
| | | 22 × 35 | 680 |
| | | 22 × 40 | 710 |
| | | 18 × 50 | 800 |
| | 120 | 22 × 45 | 900 |
| | | 25.4 × 35 | 800 |
| | | 25.4 × 40 | 830 |
| 18 × 50 | | 950 | |
| 150 | 22 × 50 | 950 | |
| 180 | 25.4 × 50 | 1100 | |