

PHL Series

• 5~35°C 5,000Times.

- Non-solvent proof.
- For Photo Flash.
- RoHS compliant.
- Halogen-free capacitors are also available.



SPECIFICATIONS

Item	Characteristics						
Rated Voltage	300 ~ 330 V _{dc}						
Operating Temperature Range	-20 ~ +55°C						
Capacitance Tolerance	-10 ~ +20%(V) (at 20°C, 120Hz)						
Leakage Current	<table border="1"> <tr> <td>∅D(mm)</td> <td>∅5~8</td> <td>∅10~</td> </tr> <tr> <td>LC(Max.)</td> <td>I = 2.0 × C</td> <td>I = 1.0 × C</td> </tr> </table> <p>Where, I:Max.Leakage current(μA) C: Nominal capacitance (μF) (at 20°C, 5 minutes)</p>	∅D(mm)	∅5~8	∅10~	LC(Max.)	I = 2.0 × C	I = 1.0 × C
∅D(mm)	∅5~8	∅10~					
LC(Max.)	I = 2.0 × C	I = 1.0 × C					
Dissipation Factor(Tanδ)	<table border="1"> <tr> <td>∅D(mm)</td> <td>∅5~8</td> <td>∅10~</td> </tr> <tr> <td>Tanδ(Max.)</td> <td>0.085</td> <td>0.06</td> </tr> </table> <p>(at 20°C, 120Hz)</p>	∅D(mm)	∅5~8	∅10~	Tanδ(Max.)	0.085	0.06
∅D(mm)	∅5~8	∅10~					
Tanδ(Max.)	0.085	0.06					
Charge and Discharge Characteristics	<p>The following specifications shall be satisfied when the capacitors are restored to 20°C after charge and discharge are repeated 5,000 times at room temperature (5 to 35°C) Discharge resistance or Xenon tube: 0.7~1.0 Ω.</p> <p>Capacitance change ≤ ±10% of the initial value Tanδ ≤ 150% of the initial specified value Leakage current ≤ 150% of the initial specified value</p>						
Shelf Life	<p>The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1000 hours at 55°C without voltage applied.</p> <p>Capacitance change ≤ ±10% of the initial value Tanδ ≤ 150% of the initial specified value Leakage current ≤ 150% of the initial specified value</p>						
Others	Satisfied characteristics EIAJ RC - 3801A						

RATINGS OF PHL Series

μF \ V _{DC}	300			315			330		
	5				5 × 16	6.3 × 10			
6.8					6.3 × 11				
10					6.3 × 15	8 × 11.5			
12.5					6.3 × 20	8 × 15			
15						8 × 17			
20						8 × 20			
30						8 × 23			
60	11.8 × 22						11.8 × 24		
80	11.8 × 27	13 × 25					11.8 × 29	13 × 27	
100	11.8 × 32	13 × 29	13.5 × 26				11.8 × 35	13 × 32	
120		13 × 34	13.5 × 30					13 × 37	
140		13 × 38	13.5 × 34					13 × 42	
160		13 × 43	13.5 × 38					13.5 × 37	
								13.5 × 41	

Note : Other case sizes, rated voltage or capacitance are also available upon request.

↑ Case Size ∅D × L(mm)

DIMENSIONS OF PHL Series

Unit(mm)

Marking : BLACK SLEEVE, WHITE INK

∅D	5	6.3	8	11.8	13	13.5
∅d	0.5	0.5	0.6	0.6	0.6	0.8
F	2.0	2.5	3.5	5.0	5.0	5.0
∅D'	∅D + 0.5 max.					
L'	L + 1.0 max.					